# Kerabit

## Kerabit LESSNOX Nature

Päivitetty 25.5.2023 Tulostettu 9.5.2024

The low-carbon status of Kerabit Nature<sup>®</sup> products is achieved, for example, by replacing some of the traditional raw materials with bio-based raw materials and recycled materials. **The carbon emissions (GWPtotal) during the manufacture of Kerabit Nature products are approximately 59 % lower than for corresponding basic products**. Apart from environmental impact, the characteristics of the products correspond to the analogous basic products. We are especially careful about the waterproofing properties – we don't compromise on them!

Kerabit LESSNOX Nature is a torchable multi-layer top membrane for multiple roofing that breaks up the hazardous nitric oxides.

The carrier consists of polyester felting. The bottom surface of the product is coated with torch-on modified bitumen and the top surface with light grey slate.

This product can be used as the top membrane of a multi-layer membrane.

See the LESSNOX-video (texts in Finnish) >

### **Technical data**

| Manufacturer / Manufactured for          | Kerabit Oy, Lohja plant  |
|--|--|
| Country of origin                        | Finland  |
| Conformity marking                       | CE   |
| Reaction to fire                         | Manufacturer's fire testing certificate  |
| Fire Classification                      | B <sub>ROOF</sub> (t2)   |
| Manufacturer's declaration of conformity | Kerabit modified bitumen roofing materials                                     |
| Quality control                          | Quality control agreement between the Plant and<br>Eurofins Expert Services Oy |
| Nominal thickness                        | n. 4,4 mm  |
| Nominal weight                           | 5000 kg/m²   |
| Weight of the supportive layer           | 170 g/m² (+/- 10 g/m²)   |
| Supportive layer                         | polyester  |
| Surface type                             | Light grey LESSNOX® slate  |
| Rolls size                               | 1 x 8 m / 8 m²   |
| Colours                                  | Light grey   |
| Packages / pallet                        | 24 rolls   |
| Weight / package                         | 40 kg  |
| Weight / pallet                          | 985 kg   |



# Kerabit

### Additional information

#### Applications

This product can be used as a top membrane of a multi-layer roofing.

#### Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.