

DECLARATION OF PERFORMANCE

Nro. 001.CPR.55511

1. Unique identification code of the product-type:

Kerabit 3200 UTL Fleece

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Dimensions	Product number
1 x 10 m	55511

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Reinforced bitumen sheets for roof waterproofing (EN 13707)
Underlay for discontinuous roofing (13859-1)
Bitumen vapour control layers (EN 13970)

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

Nordic Waterproofing Oy
Puistokatu 25 - 27, 08150 Lohja, Finland
P. 010 851 1000
www.kerabit.fi

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP 2+ (EN 13707)
AVCP 3 (EN 13859-1, EN 13970)

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

AVCP 2+

The notified factory production control certification body Eurofins Expert Services Oy No. 0809 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (No.0809-CPR-1030).

AVCP 3

The notified testing laboratory Eurofins Expert Services Oy, No. 0809 has carried out the determination of the product type on the basis of type-testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product.

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
External fire performance	B _{ROOF} (t2)	EN 13707: 2014
Reaction to fire	NPD	
Watertightness	pass	
Tensile strength <ul style="list-style-type: none"> - in longitudinal direction - in transverse direction 	750 N/50 mm, ± 150 550 N/50 mm, ± 150	
Elongation	40 %, ± 15	
Resistance to static loading	NPD	
Resistance to impact	1200 mm	
Nail shank tear resistance <ul style="list-style-type: none"> - in longitudinal direction - in transverse direction 	250 N, ± 100 300 N, ± 150	
Pliability <ul style="list-style-type: none"> - surface - backside 	-20 °C -10 °C	
Dangerous substances ^{1), 2)}	No dangerous substances	
Essential characteristics	Performance	
Reaction to fire	NPD	EN 13859-1: 2014
Watertightness	W1	
Tensile strength <ul style="list-style-type: none"> - in longitudinal direction - in transverse direction 	750 N/50 mm, ± 150 550 N/50 mm, ± 150	
Elongation	40 %, ± 15	
Nail shank tear resistance <ul style="list-style-type: none"> - in longitudinal direction - in transverse direction 	250 N, ± 100 300 N, ± 150	
Pliability	-20 °C	
After ageing Watertightness Tensile strength <ul style="list-style-type: none"> - in longitudinal direction - in transverse direction Elongation	Class W1 400 N/50 mm, ± 80 300 N/50 mm, ± 80 30 %, ± 10	
Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	NPD	EN 13970:2005
Watertightness	pass	
Tensile strength <ul style="list-style-type: none"> - in longitudinal direction - in transverse direction 	750 N/50 mm, ± 150 550 N/50 mm, ± 150	
Elongation	40 %, ± 15	
Resistance to impact	1200 bitumen/900 sand	
Joint resistance (shear)	NPD	
Pliability <ul style="list-style-type: none"> - surface - backside 	- 20 °C - 10 °C	
Nail shank tear resistance <ul style="list-style-type: none"> - in longitudinal direction - in transverse direction 	250 N, ± 100 300 N, ± 150	
Water vapor resistance after ageing	NPD	
Water vapor resistance	2,2 x 10 ¹² m ² sPa/kg	
NPD (No Performance Determined)		

- 1) No asbestos or coal tar constituents
- 2) In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Lohja 7.11.2019

A handwritten signature in black ink that reads "Pertti Nurmi". The signature is written in a cursive style with a distinct loop at the end.

Pertti Nurmi
Development and Quality Manager
Nordic Waterproofing Oy