

## Kerabit Bitumen Paint

Päivitetty 26.10.2018 Tulostettu 12.12.2019

Kerabit Bitumen Paint is a black, matt paint and care product for bitumen roofs, forming a compact and durable protective layer on drying. The product is intended for steep bitumen roofs (1:10 or steeper).

Drying time 3 – 4 hours at +20 °C. Working temperature +5...+25 °C. Bitumen paint is not thinned. Carefully mix the paint before use and during use. If you need more than one container to paint a continuous roof surface, mix all the paint you will need in one container before you start painting so as to avoid colour variation. Clean the surface to be treated from dust, dirt and loose surface particles. Spread the paint with a paintbrush or a broom. Clean the tools with white spirit.



### Technical data

<b>Manufacturer / Manufactured for</b>	Nordic Waterproofing Oy/Lohja Plant
<b>Country of origin</b>	Denmark
<b>Drying time</b>	3 - 4 hours at +20°C
<b>Need for materials</b>	0,5 - 0,7 l/m <sup>2</sup>
<b>Container Size</b>	5 and 10 l
<b>Packages / pallet</b>	60 / 24
<b>Weight / package</b>	5 / 10
<b>Weight / pallet</b>	325 / 265 kg

### Additional information

#### Applications

For painting bitumen roofing.

#### Instructions for use

Drying time 3 – 4 hours at +20 °C. Working temperature + 5...+ 25 °C. Bitumen paint is not thinned. Carefully mix the paint before use and during use. If you need more than one container to paint a continuous roof surface, mix all the paint you will need in one container before you start painting so as to avoid colour variation. Clean the surface to be treated from dust, dirt and loose surface particles. Spread the paint with a spatula. Clean the tools with white spirit.

## Prevention of environmental hazards

The product must be prevented from entering sewers, waterways or soil. Liquid waste must be transported to a waste collection point for hazardous waste, and empty, dry containers can be recycled or, if this option is unavailable, transported to a public landfill.